

# PLANA PRO - MODEL: DWP31

Recessed Ceiling Luminaires

WAC ARCHITECTURAL


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

PLANA PRO downlight using LiteBrush optical system, with RGBW chip, can achieve magic color wall washing, while having a good anti-glare effect. Mainly applicable to hotels and commercial areas.

## Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: LiteBrush® wall wash system
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

## Product Specifications


- Cut-out: Ø93mm
- Ceiling Thickness: 1mm~35mm
- Shielding Angle: 35°
- LED Type: RGBW 4in1
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: RGB+3000K Ra90
- Input: 24V DC
- Dimming: DMX512
- Net Weight: 1.0Kg without packing

## Order Model

Model	Size	Trim	LED	Driver	CCT	Beam	Reflector	Finish
<b>DWP</b> Downlight Wallwasher P series	<b>3</b> 3"	<b>1</b> Round Trim	<b>LD14</b> 14W	<b>M</b> 24V DMX512	<b>F3</b> RGBW(3000K)	<b>W</b> Wash	<b>B</b> Black	<b>WT</b> White <b>BK</b> Black

Example: DWP31-LD14M-F3WBBK

## LIGHT DISTRIBUTION



WAC Lighting  
[www.waclighting.com](http://www.waclighting.com) (US)  
[www.waclighting.net](http://www.waclighting.net) (International)

Headquarters  
 44 Harbor Park Drive • Port Washington, NY  
 Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
 TECHNOLOGY ILLUMINATED

WAC Lighting reserves the right to periodically design and update products. 2025-08-12

# PLANA PRO - MODEL: DWP41

Recessed Ceiling Luminaires

WAC ARCHITECTURAL


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

PLANA PRO downlight using LiteBrush optical system, with RGBW chip, can achieve magic color wall washing, while having a good anti-glare effect. Mainly applicable to hotels and commercial areas.

## Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: LiteBrush® wall wash system
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

## Product Specifications


- Cut-out: Ø116mm
- Ceiling Thickness: 1mm~35mm
- Shielding Angle: 35°
- LED Type: RGBW 4in1
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: RGB+3000K Ra90
- Input: 24V DC
- Dimming: DMX512
- Net Weight: 1.45Kg without packing

## Order Model

Model	Size	Trim	LED	Driver	CCT	Beam	Reflector	Finish
<b>DWP</b>	<b>4</b>	<b>1</b>	<b>LD24</b>	<b>M</b>	<b>F3</b>	<b>W</b> Wash	<b>B</b> Black	<b>WT</b> White
Downlight	4"	Round Trim	24W	24V DMX512	RGBW(3000K)			<b>BK</b> Black
Wallwasher								
P series								

Example: DWP41-LD24M-F3WBBK

## LIGHT DISTRIBUTION



WAC Lighting  
[www.waclighting.com](http://www.waclighting.com) (US)  
[www.waclighting.net](http://www.waclighting.net) (International)

Headquarters  
 44 Harbor Park Drive • Port Washington, NY  
 Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
 TECHNOLOGY ILLUMINATED