

# SLANA PRO - MODEL: AES3NC

WAC ARCHITECTURAL

Surface Mounted Luminaires


PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

## Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °, vertical  $\pm 25$  °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: COB
- LED Power: 13W (Max)
- Source Lm: 3000K 1560lm;4000K 1690lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF
- Net Weight: 1.0Kg without packing

## Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3N	C Ceiling Mounted	13 13(Max)	COB	690	EL ON-OFF	1 13 °	30	B Black S Specular	WT White
					220V AC Power Supply	2 20 °			
					DL 0-10V Dimming	3 30 °	40		
					220V AC Power Supply	4 40 °	4000K		

Example : AES3NC-13EL130BWT

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.net (International)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
TECHNOLOGY ILLUMINATED

WAC Lighting reserves the right to periodically design and update products. 2025-08-12

# SLANA PRO - MODEL: AES3NC


# WAC ARCHITECTURAL

Surface Mounted Luminaires


PROJECT :

TYPE :


## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




**MODEL :** AES3NC-13EL130SWT  
**BEAM ANGLE :** 13 °  
**POWER :** 14.9W  
**LUMENS :** 799.4 lm  
**CBCP :** /  
**EFFICACY :** 53.4 lm /W



**MODEL :** AES3NC-13EL230SWT  
**BEAM ANGLE :** 20 °  
**POWER :** 15.2W  
**LUMENS :** 906 lm  
**CBCP :** /  
**EFFICACY :** 59.6 lm /W



**MODEL :** AES3NC-13EL330SWT  
**BEAM ANGLE :** 30 °  
**POWER :** 15.26W  
**LUMENS :** 911 lm  
**CBCP :** /  
**EFFICACY :** 59.7 lm /W



**MODEL :** AES3NC-13EL430SWT  
**BEAM ANGLE :** 40 °  
**POWER :** 15.1W  
**LUMENS :** 856 lm  
**CBCP :** /  
**EFFICACY :** 56.8 lm /W

# SLANA PRO - MODEL: AES3SC

WAC ARCHITECTURAL

Surface Mounted Luminaires


PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

## Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °; vertical ±25 °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: COB
- LED Power: 18W (Max)
- Source Lm: 3000K 2160lm;4000K 2340lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF/0-10V
- Net Weight: 1.0Kg without packing

## Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3S	C Ceiling Mounted	18 18(Max)	COB	1500	EL ON-OFF	1 19 °	30	B Black S Specular	WT White
					220V AC Power Supply	2 26 °			
					DL 0-10V Dimming	3 38 °	40		
					220V AC Power Supply	5 52 °	4000K		

Example : AES3SC-18EL130BWT

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.net (International)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
TECHNOLOGY ILLUMINATED

WAC Lighting reserves the right to periodically design and update products. 2025-08-12

# SLANA PRO - MODEL: AES3SC

# WAC ARCHITECTURAL


Surface Mounted Luminaires

PROJECT :


TYPE :

Accessories


## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




**MODEL :** AES3SC-18EL130BWT  
**BEAM ANGLE :** 19 °  
**POWER :** 19.1W  
**LUMENS :** 1599 lm  
**CBCP :** /  
**EFFICACY :** 83.5 lm /W



**MODEL :** AES3SC-18EL230BWT  
**BEAM ANGLE :** 26 °  
**POWER :** 19.1W  
**LUMENS :** 1656 lm  
**CBCP :** /  
**EFFICACY :** 88.8 lm /W



**MODEL :** AES3SC-18EL330BWT  
**BEAM ANGLE :** 38 °  
**POWER :** 19.1W  
**LUMENS :** 1699 lm  
**CBCP :** /  
**EFFICACY :** 88.9 lm /W



**MODEL :** AES3SC-18EL530BWT  
**BEAM ANGLE :** 52 °  
**POWER :** 19.2W  
**LUMENS :** 1592 lm  
**CBCP :** /  
**EFFICACY :** 82.8 lm /W

# SLANA PRO - MODEL: AES3MC

WAC ARCHITECTURAL

Surface Mounted Luminaires


PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The Slana Pro surface mounted tube lights are more decorative in building lighting, using ceiling and suspension installation. The exquisite and meticulous appearance and structural design, excellent optical performance, and flexible humanized accessories can bring users a perfect light environment experience. The lighting fixtures have angle adjustment function and are suitable for functional lighting in public high spaces.

## Product Features

- Body Material: Die cast aluminum end caps and lamp bodies
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 355 °; vertical  $\pm 25$  °
- Accessories: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: COB
- LED Power: 33W (Max)
- Source Lm: 3000K 4180lm ; 4000K 4318lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K / 4000K , Ra80
- SDCM: 3 SDCM
- Input: 220V/AC , 50/60Hz
- Dimming: ON-OFF/0-10V (Conduct compatibility testing in advance)
- Net Weight: 2.5Kg without packing

## Order Model

Model	Comment	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Reflector	Finish
AES3M	C Ceiling Mounted	33 33(Max)	COB	2500	EL ON-OFF 220V AC Power Supply	1 19 ° 2 26 °	30 3000K	B Black S Specular	WT White
					DL 0-10V Dimming 220V AC Power Supply	3 38 ° 5 52 °			

Example : AES3MC-33EL130BWT

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.net (International)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
TECHNOLOGY ILLUMINATED

WAC Lighting reserves the right to periodically design and update products. 2025-08-12

# SLANA PRO - MODEL: AES3MC

# WAC ARCHITECTURAL


## Surface Mounted Luminaires

PROJECT :


TYPE :

Accessories


### LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




**MODEL :** AES3MC-33EL130SWT  
**BEAM ANGLE :** 19°  
**POWER :** 37.2W  
**LUMENS :** 3550 lm  
**CBCP :** /  
**EFFICACY :** 95.4 lm /W



**MODEL :** AES3MC-33EL230SWT  
**BEAM ANGLE :** 26°  
**POWER :** 37.3W  
**LUMENS :** 3498 lm  
**CBCP :** /  
**EFFICACY :** 93.6 lm /W



**MODEL :** AES3MC-33EL330SWT  
**BEAM ANGLE :** 38°  
**POWER :** 37.5W  
**LUMENS :** 3694 lm  
**CBCP :** /  
**EFFICACY :** 98.6 lm /W



**MODEL :** AES3MC-33EL530SWT  
**BEAM ANGLE :** 52°  
**POWER :** 37.1W  
**LUMENS :** 3329 lm  
**CBCP :** /  
**EFFICACY :** 89.7 lm /W