

# ULTRA - MODEL: ASLN32

## Ceiling Mount Luminaires

WAC ARCHITECTURAL


PROJECT:

TYPE:

### Product Image



### Line Drawing



### Product Description

The ULTRA series LED circular exposed tube lamp adopts a modular design, and on-site lamps can be freely disassembled and replaced with reflectors and lamp bodies, thereby achieving free switching of various specifications and lighting methods. In terms of optics, a brand new hidden light technology is adopted, which has good anti glare performance and color consistency control, and has a comfortable lighting effect. It is mainly suitable for indoor places such as hotels, villas, and commercial spaces.

### Product Features

- Body Material: Aluminum alloy die-casting body
- Optical System: Lens+ Anti glare reflector
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: See accessory list
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

### Product Specifications

- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 3000K 1000LM,4000K 1100LM;  
2700K: 8W 682 lm; 7W 758 lm; 10W 1080 lm; 13W 1404 lm  
3000K: 8W 720 lm; 7W 800 lm; 10W 1150 lm; 13W 1495 lm  
3500K: 8W 752 lm; 7W 835 lm; 10W 1195 lm; 13W 1554 lm  
4000K: 8W 765 lm; 7W 850 lm; 10W 1210 lm; 13W 1573 lm  
5000K: 8W 774 lm; 7W 860 lm; 10W 1220 lm; 13W 1586 lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, CRI≥90
- Input: 220V AC /50Hz
- Dimming: No Dimming/0-10V(Must conduct compatibility testing with the project site in advance)
- Net Weight: 0.36Kg without packing

### Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
ASLN	3	2	LM08 COB 8W	E On-Off	S 8°	27 2700K	B Black	WT
Surface	3"	Ronnd	LM07 COB 7W	D 0-10V	N 13°	30 3000K	S Specular	White
Mounted		Trimless	LM10 COB 10W	Dimming	1 18°	35 3500K		BK
Downlight			LM13 COB 13W		2 28°	40 4000K		Black
N series					3 36°	50 5000K		
					5 50°			

Example: ASLN32-LM07EN30SWT

Note: 8°, 13°, and 18° are factory default with honeycomb grilles.

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.net (International)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC GROUP  
TECHNOLOGY ILLUMINATED

# ULTRA - MODEL: ASLN32





## Ceiling Mount Luminaires

WAC ARCHITECTURAL

PROJECT:


TYPE:

### Accessory


<b>ALENS-11-BEL</b> Striped glass lenses 	<b>ALENS-11-BSL-ULTRA</b> Soft glass lenses 	<b>ALENS-11-FR</b> Frosted glass lenses 	<b>ALENS-11-HCL-ULTRA</b> Borderless honeycomb grille 
---	--	---	--

Note: Up to one optical accessory can be added; Among them, 8°, 13°, and 18° are factory default with borderless honeycomb grilles.


### LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




<b>MODEL:</b>	ASLN32-LM07E-N30SWT
<b>BEAM ANGLE:</b>	13°
<b>POWER:</b>	9W
<b>LUMENS:</b>	466 lm
<b>CBCP:</b>	5571cd
<b>EFFICACY:</b>	52 lm/W




<b>MODEL:</b>	ASLN32-LM10E-N30SWT
<b>BEAM ANGLE:</b>	13°
<b>POWER:</b>	11W
<b>LUMENS:</b>	520 lm
<b>CBCP:</b>	6220cd
<b>EFFICACY:</b>	47 lm/W




<b>MODEL:</b>	ASLN32-LM13EN30SWT
<b>BEAM ANGLE:</b>	13°
<b>POWER:</b>	16W
<b>LUMENS:</b>	676 lm
<b>CBCP:</b>	8086cd
<b>EFFICACY:</b>	42 lm/W




<b>MODEL:</b>	ASLN32-LM07E130SWT
<b>BEAM ANGLE:</b>	18°
<b>POWER:</b>	9W
<b>LUMENS:</b>	721 lm
<b>CBCP:</b>	5316cd
<b>EFFICACY:</b>	80 lm/W




<b>MODEL:</b>	ASLN32-LM10E130SWT
<b>BEAM ANGLE:</b>	18°
<b>POWER:</b>	11W
<b>LUMENS:</b>	817 lm
<b>CBCP:</b>	6028cd
<b>EFFICACY:</b>	74 lm/W



<b>MODEL:</b>	ASLN32-LM13E130SWT
<b>BEAM ANGLE:</b>	18°
<b>POWER:</b>	16W
<b>LUMENS:</b>	1062 lm
<b>CBCP:</b>	7836cd
<b>EFFICACY:</b>	66 lm/W



<b>MODEL:</b>	ASLN32-LM07E230SWT
<b>BEAM ANGLE:</b>	28°
<b>POWER:</b>	9W
<b>LUMENS:</b>	715 lm
<b>CBCP:</b>	3052cd
<b>EFFICACY:</b>	79 lm/W



<b>MODEL:</b>	ASLN32-LM10E230SWT
<b>BEAM ANGLE:</b>	28°
<b>POWER:</b>	11W
<b>LUMENS:</b>	796 lm
<b>CBCP:</b>	3396cd
<b>EFFICACY:</b>	72 lm/W


# ULTRA - MODEL: ASLN32

## Ceiling Mount Luminaires


# WAC ARCHITECTURAL

PROJECT:


TYPE:




**MODEL:** ASLN32-LM13E230SWT  
**BEAM ANGLE:** 28°  
**POWER:** 15W  
**LUMENS:** 1035 lm  
**CBCP:** 4511cd  
**EFFICACY:** 69 lm/W




**MODEL:** ASLN32-LM07E330SWT  
**BEAM ANGLE:** 36°  
**POWER:** 9W  
**LUMENS:** 643 lm  
**CBCP:** 1497cd  
**EFFICACY:** 71 lm/W




**MODEL:** ASLN32-LM10E330SWT  
**BEAM ANGLE:** 36°  
**POWER:** 11W  
**LUMENS:** 804 lm  
**CBCP:** 1857cd  
**EFFICACY:** 73 lm/W




**MODEL:** ASLN32-LM13E330SWT  
**BEAM ANGLE:** 36°  
**POWER:** 15W  
**LUMENS:** 1024lm  
**CBCP:** 2375cd  
**EFFICACY:** 68 lm/W




**MODEL:** ASLN32-LM07E530SWT  
**BEAM ANGLE:** 50°  
**POWER:** 9W  
**LUMENS:** 425 lm  
**CBCP:** 574cd  
**EFFICACY:** 47 lm/W



**MODEL:** ASLN32-LM10E530SWT  
**BEAM ANGLE:** 50°  
**POWER:** 119W  
**LUMENS:** 532 lm  
**CBCP:** 717cd  
**EFFICACY:** 48 lm/W



**MODEL:** ASLN32-LM13E530SWT  
**BEAM ANGLE:** 50°  
**POWER:** 15W  
**LUMENS:** 677 lm  
**CBCP:** 914cd  
**EFFICACY:** 45 lm/W



**MODEL:** ASLN32-LM08ES30SWT  
**BEAM ANGLE:** 8°  
**POWER:** 10W  
**LUMENS:** 375lm  
**CBCP:** 9280cd  
**EFFICACY:** 38 lm/W