


FQ Tunable White 4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL



Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____



PRODUCT DESCRIPTION
 FQ (Function + Quality) Experience simplicity and versatility with FQ 4" recessed luminaires. The fixtures merge modern design with world-class performance to achieve the ultimate in function and flexibility. Enjoy the benefits of two fixtures in one with Tunable White 1800-4000K and Dim-to-Warm 3000K-1800K features built into each luminaire, allowing you to customize the best light to illuminate dining areas, great rooms, primary bedrooms, kitchens, and baths on the fly. Deep regressed light sources deliver a glare-free, quiet ceiling aesthetic for a clean architectural look while providing a robust output from a diminutive source.

SPECIFICATIONS

Construction:	Durable die-cast self flanged aluminum construction
Mounting:	Heavy gauge retention clips support trim firmly Ceiling cut out (Round): Trim \varnothing 4 3/4" \bigcirc Trimless \varnothing 4 3/4" \bigcirc Ceiling cut out (Square): Trim 4 3/4" x 4 3/4" \square Trimless 4 3/4" x 4 3/4" \square Accommodates 1/2" - 1" ceiling thickness
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Input:	Universal 120-277V AC, 50/60 Hz
Dimming:	2CH 0-10V, DMX512-A: 100-0.1%
Maximum Delivered Output:	Up to 1,367 lm (Round Asymmetric, 26W, 4000K, CRI 90)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Wet location listed, Title 24 JA8 Compliant
Warranty:	5 year WAC Lighting guaranteed warranty



Model	Beam	Lumens	CBCP	Color Temp	CRI
		Ref Output*	Ref Output*		
R4FRWT Round Trim	A Asym	Round	1210	N/A	TW 1800K-4000K 90
R4FRWL Round Trimless		Square	1080	N/A	
R4FSWT Square Trim					
R4FSWL Square Trimless					

Lumens and CBCP are reference values for a trim fixture with 3 housing set to 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.

FQ Tunable White 4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

ORDERING INFORMATION

CONFIGURATION TABLE		
Model	Color Temperature & CRI	Reflector Finish
R4FRWT	TW - 1800K-4000K	BK - BLACK
R4FRWL		DB - DARK BRONZE
R4FSWT		HZ - HAZE
R4FSWL		HZWT - HAZE/WHITE WT - WHITE

R4FRWT-TW-__

Example: R4FRWT-TW-WT

ORDERING NOTES
1. The "Haze/White" finish is only available on trimmed fixtures (R4FRWT, R4FSWT).
2. The "Haze" finish is only available on trimless fixtures (R4FRWL, R4FSWL)

Housings	Model	Control Options	Power
New Construction IC Airtight - Round & Square Trim	R4FBNT-TW	X DMX512-A Z 0-10V	1 14W IC 2 19W IC 3 26W IC
New Construction IC Airtight - Round Trimless	R4FRNL-TW	X DMX512-A Z 0-10V	1 14W IC 2 19W IC 3 26W IC
New Construction IC Airtight - Square Trimless	R4FSNL-TW	X DMX512-A Z 0-10V	1 14W IC 2 19W IC 3 26W IC
Remodel Non-IC Round Trimless	R4FRRL-TW	X DMX512-A Z 0-10V	1 13W Non-IC 2 19W Non-IC 3 25W Non-IC
Remodel Non-IC Square Trimless	R4FSRL-TW	X DMX512-A Z 0-10V	1 13W Non-IC 2 19W Non-IC 3 25W Non-IC
Remodel IC Round & Square Trim	R4FBR2T-TW	X DMX512-A Z 0-10V	1 14W IC
Remodel Non-IC Round & Square Trim	R4FBRT-TW	X DMX512-A Z 0-10V	1 14W Non-IC 2 19W Non-IC 3 26W Non-IC

ACCESSORIES	
LENS-16-HCM	<i>Honeycomb Louver</i>
LENS-16P-CRL-BK	<i>Cross Louver</i>
LENS-16AMB	<i>Amber Lens</i>
LENS-16RED	<i>Red Lens</i>
LENS-16BLU	<i>Blue Lens</i>
LENS-16GRN	<i>Green Lens</i>
LENS-16SPR	<i>Spread Lens</i>
LENS-16BEL	<i>Beam Elongating Lens</i>

R4F__-TW__
 Example: R4FBNT-TWX-2

FQ Tunable White

4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

FEATURES

<p>Optics:</p> <ul style="list-style-type: none"> • High lumen output across the full Tunable White CCT range of 1800K - 4000K • Powerful glare control due to the fixtures 30° shielding angle, 45° vertical tilting, and 360° horizontal rotation 	<p>Construction:</p> <ul style="list-style-type: none"> • Two piece die-cast aluminum constructed body and trim
<p>LED:</p> <ul style="list-style-type: none"> • High output COB LED with a 3-step Mac Adam ellipse • Rated operational life of 50,000 hours at L70 (LED maintains 70% of its initial delivered lumens when brand new for 50,000 hours of use.) 	<p>Trim and Reflector:</p> <ul style="list-style-type: none"> • Available in a wall wash (asymmetric) beam angle for even wall illumination both vertically and horizontally
<p>Electrical:</p> <ul style="list-style-type: none"> • Input power is universal 120-277VAC and 50/60 Hz • Available in 14W, 19W, and 26W power levels 	<p>Installation:</p> <ul style="list-style-type: none"> • Light engine is mounted onto the trim using springs that allow for easy replacement • Heavy gauge retention clips firmly support the trim within the housing
<p>Dimming:</p> <ul style="list-style-type: none"> • DMX512-A and 2 Channel 0-10V dimming are available • DMX512-A and 2 Channel 0-10V dimming are both capable of a range of 100 - 0.1% 	<p>Warranty:</p> <ul style="list-style-type: none"> • WAC Architectural limited warranty up to 5 years • Full warranty found at: wacighting.com/warranty
<p>Notes:</p> <ul style="list-style-type: none"> • The White, Black, and Dark Bronze finishes are all electrostatically powder coated • The Haze finish is enamel coated 	

FQ Tunable White

4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____


PERFORMANCE DATA

Polar Candela Distribution Charts

Samples shown from a trim fixture with 3 housing set to 3000K.


ROUND

Asymmetric Beam



SQUARE

Asymmetric Beam



FQ Tunable White

4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

UGR values shown are calculated for a Round Trim Asymmetric (Asym) beam fixture with 3 housing at 3000K and 90 CRI. General performance of other beam angles shown below.

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	24.4	25.6	24.6	25.8	26.0	25.8	27.1	26.1	27.2	27.4	
3H	24.7	25.9	25.0	26.1	26.3	26.1	27.3	26.4	27.5	27.7	
4H	24.8	25.9	25.1	26.2	26.4	26.2	27.2	26.5	27.5	27.7	
6H	24.9	25.9	25.2	26.1	26.4	26.1	27.1	26.4	27.4	27.7	
8H	24.8	25.8	25.2	26.1	26.4	26.1	27.0	26.4	27.3	27.6	
12H	24.8	25.7	25.1	26.0	26.3	26.0	27.0	26.4	27.2	27.5	
4H	2H	24.7	25.8	25.0	26.1	26.3	25.9	27.0	26.2	27.3	27.5
	3H	25.2	26.2	25.6	26.5	26.8	26.4	27.3	26.7	27.6	27.9
	4H	25.4	26.3	25.8	26.6	26.9	26.5	27.3	26.8	27.6	27.9
	6H	25.5	26.2	25.9	26.6	26.9	26.4	27.2	26.8	27.5	27.9
	8H	25.5	26.2	25.9	26.5	26.9	26.4	27.1	26.8	27.5	27.8
	12H	25.4	26.1	25.9	26.4	26.8	26.4	27.0	26.8	27.4	27.8
8H	4H	25.4	26.1	25.8	26.5	26.9	26.4	27.1	26.8	27.5	27.9
	6H	25.6	26.1	26.0	26.5	27.0	26.5	27.0	26.9	27.4	27.9
	8H	25.6	26.1	26.1	26.5	27.0	26.4	26.9	26.9	27.4	27.8
	12H	25.6	26.0	26.1	26.4	26.9	26.4	26.8	26.9	27.3	27.8
12H	4H	25.4	26.0	25.8	26.4	26.8	26.4	27.0	26.8	27.4	27.8
	6H	25.6	26.1	26.0	26.5	26.9	26.4	26.9	26.9	27.4	27.8
	8H	25.6	26.0	26.1	26.5	26.9	26.4	26.9	26.9	27.3	27.8

Round Fixture	Angle	UGR Range
Asymmetric	-	≤28

Square Fixture	Angle	UGR Range
Asymmetric	-	≤26

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

Lumens & CBCP Multiplier		Color Temperature					
TWA (1800K - 4000K)	Housing Power Level	1800K	2200K	2700K	3000K	3500K	4000K
	1 (14W)	0.42	0.48	0.53	0.56	0.59	0.63
	2 (19W)	0.59	0.67	0.74	0.78	0.83	0.88
	3 (26W)	0.76	0.86	0.95	1.00	1.07	1.13


FQ Tunable White
4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL


Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

DIMENSIONAL DIAGRAMS


Round Trim (R4FRWT)




Round Trimless (R4FRWL)



Square Trim (R4FSWT)



Square Trimless (R4FSWL)




FQ Tunable White
4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL


Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

DIMENSIONAL DIAGRAMS


New Construction - Round Trim



New Construction - Round Trimless



New Construction - Square Trim



New Construction - Square Trimless

