


Ligne III

Wall Wash

LWW24 | LWW48

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____





LINE DRAWING

24" Length



48" Length



PRODUCT DESCRIPTION

The LIGNE III features a specialized lens or polarized optical system combined with an optimized LED arrangement, delivering uniform wall illumination with no dark spots or glare. It offers high-efficiency heat dissipation, low energy consumption, and a soft anti-glare lighting effect. With a DC 48V input, fixtures can be connected end-to-end for continuous installation. Ideal for recessed linear wall-washing applications in offices, exhibition halls, hotels, and commercial public areas.

SPECIFICATIONS

Construction:	Durable die-cast aluminum construction
Mounting:	Surface mounted
Light Source:	3-step Mac Adam Ellipse Rated life of 50,000 hours at L70
Input:	48 VDC
Maximum Delivered Intensity:	Up to 7,811 cd (Asymmetric, 48in, 5000K)
Maximum Delivered Output:	Up to 2,929 lm (Asymmetric, 48in, 5000K)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed
Warranty:	5 year WAC Lighting guaranteed warranty

BEAM ANGLES



FINISHES



Model	Length	Beam	Power	Lumens Ref Output*	CBCP	Color Temp	CRI
LWW Wall Wash	24in 48in	A Asym	12W 24W	1276 2615	3475 6974	927 - 2700K 930 - 3000K 935 - 3500K 940 - 4000K	90

Lumens and CBCP are reference values for 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.

Ligne III

Wall Wash

LWW24 | LWW48

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

ORDERING INFORMATION

CONFIGURATION TABLE			
Model & Power	Beam Angle	Color Temperature & CRI	Housing Finish
LWW24 LWW48	A - Asymmetric	927 - 2700K - 90	BK - BLACK
		930 - 3000K - 90	
		935 - 3500K - 90	WT - WHITE
		940 - 4000K - 90	

LWW __ -A __ - __

Example: LWW12-A927-BK

ACCESSORIES	
LWW24-HCM-WT	<i>Honeycomb Louver - White, 24in</i>
LWW24-HCM-BK	<i>Honeycomb Louver - Black, 24in</i>
LWW48-HCM-WT	<i>Honeycomb Louver - White, 48in</i>
LWW48-HCM-BK	<i>Honeycomb Louver - Black, 48in</i>

ORDERING NOTES
<ol style="list-style-type: none"> Holder included with the Honeycomb Louver. The Honeycomb Louver holder is available in Black and White finishes. The Honeycomb Louver itself is only available in Black finish.

Ligne III

Wall Wash

LWW24 | LWW48

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____


PERFORMANCE DATA

Polar Candela Distribution Charts

Samples shown from a fixture set to 3000K.


LWW24

Asymmetric Beam (Asym)



LWW48

Asymmetric Beam (Asym)



Ligne III

Wall Wash

LWW24 | LWW48

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

Samples shown from a fixture set to 3000K.

24in Fixture	Angle	UGR Range
Asymmetric	-	≤26

48in Fixture	Angle	UGR Range
Asymmetric	-	≤25

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

Color Temperature				
2700K	3000K	3500K	4000K	5000K
0.96	1.00	1.02	1.07	1.12