

RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____


Project: _____

Catalog#: _____

Location: _____



LINE DRAWING



PRODUCT DESCRIPTION

The RUYI Pro is a compact architectural LED fixture designed to highlight building facades and window frames. Its durable die-cast aluminum housing with high-temperature powder coating and ratings of IP68 and IK09 ensures reliable performance in outdoor environments. The fixture features an adjustable beam angle, allowing precise illumination across bay windows or façade details. A high-transmittance lens delivers efficient, evenly distributed lighting for modern architectural applications.

SPECIFICATIONS

Construction:	Durable die-cast aluminum body
Mounting:	Outdoor installation
Light Source:	High output 3-step Mac Adam Ellipse Rated life of 50,000 hours at L70
Input:	24 VDC
Power:	24W
Dimming:	On/Off, 0-10V, DMX512-A
Maximum Delivered Intensity:	Up to 1,240 cd (12°, 3000K)
Maximum Delivered Output:	Up to 380 lm (12°, 3000K)
Operating Temperature:	-4°F to 122°F (-20°C to 50°C)
Standards:	UL & cUL Wet location listed, IP68, IK09
Warranty:	5 year WAC Lighting guaranteed warranty

Model	Beam	Lumens Ref Output*	CBCP	Efficacy (lm/W)	Color Temp
WL-ADJ	Adj 7-13°	380	1240	16	930-3000K

*Lumens and CBCP are reference values for 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.

RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

ORDERING INFORMATION

CONFIGURATION TABLE		
Model & Power	Color Temperature & CRI	Housing Finish
WL-ADJ	930 - 3000K - 90 CRI	BK - BLACK WT - WHITE SS - STAINLESS

WL-ADJ-930-__

Example: WL-ADJ-930-BK

ACCESSORIES	
WL-RBOX-BK	Window Light Block Out Box - Black
WL-LW01-BK	Window Light Lead In Cable - 1ft
WL-LW05-BK	Window Light Lead In Cable - 5ft
WL-LW10-BK	Window Light Lead In Cable - 10ft
WL-LW20-BK	Window Light Lead In Cable - 20ft
WL-LW25-BK	Window Light Lead In Cable - 25ft
WL-JC01-BK	Window Light Jumper Cable - 1ft
WL-JC05-BK	Window Light Jumper Cable - 5ft
WL-JC10-BK	Window Light Jumper Cable - 10ft
WL-JC20-BK	Window Light Jumper Cable - 20ft
WL-JC25-BK	Window Light Jumper Cable - 25ft
WL-JCY01-BK	Window Light 3 Way Jumper Cable - 1ft
WL-JCY05-BK	Window Light 3 Way Jumper Cable - 5ft
WL-JCY10-BK	Window Light 3 Way Jumper Cable - 10ft
WL-JCY20-BK	Window Light 3 Way Jumper Cable - 20ft
WL-JCY25-BK	Window Light 3 Way Jumper Cable - 25ft
WL-JC-ENDCAP-BK	Window Light Cable End Cap

RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

FEATURES

<p>Optics:</p> <ul style="list-style-type: none"> • High transmittance lens allows for powerful illumination of building facades, windows, and other outdoor applications 	<p>Construction:</p> <ul style="list-style-type: none"> • Suitable for outdoor applications with ratings of IP68 and IK09 • Fixture body is die-cast aluminum • Trim cover plate is made of 316 stainless steel
<p>LED:</p> <ul style="list-style-type: none"> • High output LED with a 3-step Mac Adam ellipse • Rated operational life of 50,000 hours at L70 (LED maintains 70% of its initial delivered lumens when brand new for 50,000 hours of use.) 	<p>Trim and Reflector:</p> <ul style="list-style-type: none"> • Beam angle is adjustable from 7° to 13°
<p>Electrical:</p> <ul style="list-style-type: none"> • Input power is 24 VDC • Available in a 24W power level 	<p>Installation:</p> <ul style="list-style-type: none"> • Able to be surface mounted or recessed depending on application
<p>Dimming:</p> <ul style="list-style-type: none"> • 0-10V and DMX512-A are both available 	<p>Warranty:</p> <ul style="list-style-type: none"> • WAC Architectural limited warranty up to 5 years • Full warranty found at: waclighting.com/warranty
<p>Notes:</p> <ul style="list-style-type: none"> • The Black and White finish is electrostatically powder coated 	

RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____

Project: _____

Catalog#: _____


Location: _____

PERFORMANCE DATA


Polar Candela Distribution Charts

Samples shown from a fixture set to 3000K.

Adjustable Beam - Spot



Adjustable Beam - Narrow Flood



RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

Samples shown from an Adjustable fixture set to 3000K.

Fixture	Angle	UGR Range
Adjustable	7°	≤22
Adjustable	13°	≤28

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

Color Temperature				
2700K	3000K	3500K	4000K	5000K
0.96	1.00	1.02	1.07	1.12

RUYI Pro - Adjustable

Static White

WL-ADJ

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

DIMENSIONAL DIAGRAMS

