

Stealth Framing Projector

Large - Adjustable

WTK-1224 | WHK-1224 | MO-1224

Fixture Type: _____


Project: _____

Catalog#: _____

Location: _____



LINE DRAWING



PRODUCT DESCRIPTION

The sleek, stylish luminaire projects a square, rectangular or circular area of light with crisp lines to frame or highlight art objects, providing maximum visual impact. Like a quality camera lens, the innovative projector contains adjustable lenses as well as shims to frame a sharp accenting light the width and length of the object. It can zoom in for a closeup or zoom out to frame larger pieces of art.

SPECIFICATIONS

Construction:	Die-cast aluminum with optical glass lenses
Mounting:	Track mounted; ceiling or wall mounted
Light Source:	Integrated LED, High output 3-step Mac Adam Ellipse Rated life of 50,000 hours at L70
Input:	Universal 120-277V AC, 50/60 Hz
Power:	24W
Dimming:	ELV, TRIAC (120V only): 100 - 5%
Maximum Delivered Intensity:	Up to 9,650 cd (4000K)
Maximum Delivered Output:	Up to 650 lm (4000K)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed
Warranty:	5 year WAC Lighting guaranteed warranty

FINISHES



Model	Color Temp	Lumens	CBCP	CRI	
WTK-1224 WHK-1224 MO-1224 <small>Ø2 9/16" Ø65mm</small>	927	13°	620	9,059	90
		35°	620	2,257	
	930	13°	653	9,536	
		35°	653	2,376	
	935	13°	685	10,012	
		35°	685	2,495	
	940	13°	705	10,298	
		35°	705	2,566	



Stealth Framing Projector

Large - Adjustable

WTK-1224 | WHK-1224 | MO-1224

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____

ORDERING INFORMATION

CONFIGURATION TABLE		
Model & Power	Color Temperature & CRI	Fixture Finish
WTK-1224 (120V)	927 - 2700K - 90	BK - BLACK
WHK-1224 (277V)	930 - 3000K - 90	WT - WHITE
MO-1224	935 - 3500K - 90	
	940 - 4000K - 90	

W __ - ____ - __

Example: WTK-1224-940-BK

MO-1224- ____ - __

Example: MO-1224-930-WT

ORDERING NOTES

1. The WTK-1224 fixture is 120V and the WHK-1224 fixture is 277V. Both fixtures are 12W and track mounted.
2. The MO-1224 fixture is a 12W and 120-277V ceiling mounted monopoint fixture.

Stealth Framing Projector

Large - Adjustable

WTK-1224 | WHK-1224 | MO-1224

Fixture Type: _____

Project: _____

Catalog#: _____

Location: _____


PERFORMANCE DATA

Polar Candela Distribution Charts


Samples shown with a 24W fixture set to 3000K.

Adjustable

Minimum Zoom - 13°



Maximum Zoom - 35°



Unified Glare Rating (UGR) Table

General performance of fixtures at 3000K and 90 CRI.

Round Fixture	Angle	UGR Range
Minimum Zoom	13°	≤ 0
Maximum Zoom	35°	≤ 0
Fixed	50°	≤ 0