


Mere High Power COB

WTK-37S | WHK-37S | MO-N37S | MO-R37S

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____



LINE DRAWING



PRODUCT DESCRIPTION

Smarter, more flexible, and more versatile MERE track and monopoint lighting. MERE offers a wide range of optical configurations, color temperatures, accessories, and even a DIY intelligent control module.

SPECIFICATIONS

Construction:	Injection molded polycarbonate low glare trim
Mounting:	Track mounted (WTK, WHK); ceiling mounted (MO) Ceiling cut out: $\varnothing 4\frac{1}{4}$ " (MO-N (Spackle Plate), MO-R) $\varnothing 2\frac{1}{2}$ " (MO-N (Non-Spackle Plate)) Accommodates $\frac{1}{2}$ " - 2" ceiling thickness
Light Source:	High output 2-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Input:	Universal 120-277 VAC, 50/60 Hz
Power:	21W (V beam only), 28W
Dimming:	Track (120V only): ELV, TRIAC : 100 - 1% Monopoint (120-277 VAC): ELV, TRIAC, 0-10V: 100 - 1%
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL
Warranty:	5 year WAC Lighting guaranteed warranty

BEAM ANGLES



FINISHES



Model	Beam	Wattage	Lumens Ref Output*	CBCP	Color Temp	CRI
WTK-37S WHK-37S MO-N37S MO-R37S	V 8°	21W	1,823	46,859	927 - 2700K 930 - 3000K 935 - 3500K 940 - 4000K	90
	S 13°	28W	2,807	39,788		
	N 23°	28W	2,729	14,120		
	M 34°	28W	2,785	6,481		
	W 56°	28W	2,409	3,061		
	A Asym	28W	2,534	N/A		

Lumens and CBCP are reference values for fixtures measured at 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.



Mere High Power COB

WTK-37S | WHK-37S | MO-N37S | MO-R37S

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

ORDERING INFORMATION

CONFIGURATION TABLE			
Model & Power	Beam Angle	Color Temperature & CRI	Housing Finish
WTK-37S (120V)	V - Very Narrow	927 - 2700K - 90	BK - BLACK
WHK-37S (277V)	S - Spot	930 - 3000K - 90	WT - WHITE
MO-N37S (120-277V)	N - Narrow Flood	935 - 3500K - 90	
MO-R37S (120-277V)	M - Medium Flood	940 - 4000K - 90	
	W - Wide Flood		
	A - Asym (Wall Wash)		

W_K-37S-_____

Example: WTK-37S-S930WT

MO-_37S-_____

Example: MO-N37S-M930BK

ACCESSORIES	
ACC-LENS-A-37S	WALL WASH LENS 37S
ACC-LENS-EE-37S	ELONGATING BEAM LENS 37S
ACC-LENS-SS-37S	DIFFUSOR LIGHT 37S
ACC-LENS-MM-37S	DIFFUSOR MEDIUM 37S
ACC-LENS-LL-37S	DIFFUSOR HEAVY 37S
ACC-LENS-SQ-37S	SQUARE BEAM LENS 37S
ACC-LENS-S-37S	SPOT BEAM LENS 37S
ACC-LENS-N-37S	NARROW FLOOD BEAM LENS 37S
ACC-LENS-M-37S	MEDIUM FLOOD BEAM LENS 37S
ACC-LENS-F-37S	FLOOD BEAM LENS 37S
ACC-SNT-37S-BK	SNOOT 37S BLACK
ACC-SNT-37S-WT	SNOOT 37S WHITE
ACC-HCL-37S	HONEYCOMB 37S
ACC-BD-37S-BK	BARN DOOR 37S BLACK
ACC-BD-37S-WT	BARN DOOR 37S WHITE

ORDERING NOTES

- The WTK-37S fixture is 120V and the WHK-37S fixture is 277V. Both fixtures are track mounted.
- The MO-N37S fixture is a ceiling mounted monopoint fixture for New Construction installations. The MO-R37S fixture is a ceiling mounted monopoint fixture for Remodel installations.

Mere High Power COB

WTK-37S | WHK-37S | MO-N37S | MO-R37S


Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

PERFORMANCE DATA


Polar Candela Distribution Charts

Samples shown with a 38W fixture set to 3000K.


Wall Wash Beam: Asymmetric




Narrow Flood Beam: 23° Beam




Very Narrow Beam: 8° Beam




Medium Flood Beam: 34° Beam



Spot Beam: 13° Beam



Wide Flood Beam: 56° Beam



Mere
High Power COB

WTK-37S | WHK-37S | MO-N37S | MO-R37S

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

General performance of fixtures at 3000K and 90 CRI shown below.

Round Fixture	Angle	UGR Range
Wall Wash	Asymmetric	≤20
Very Narrow	8°	≤8
Spot	13°	≤10
Narrow Flood	23°	≤11
Medium Flood	34°	≤19
Wide Flood	56°	≤18

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

Color Temperature			
2700K	3000K	3500K	4000K
0.93	1.00	1.07	1.14