

CUBE

5" Double Wall Mount - Color Changing

DC-WD05

Fixture Type: _____


Project: _____

Catalog#: _____

Location: _____



LINE DRAWING



PRODUCT DESCRIPTION

The Cube Architectural Color Changing features a state of the art LED color and CCT tuning technology. Controlled via DMX-512A input with pendant, ceiling, and wall mounting options, the Cube Architectural provides top-notch illumination for both interior and exterior spaces.

SPECIFICATIONS

Construction:	Durable die-cast aluminum construction
Mounting:	Wall mounted
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
CCT Range:	1800 - 6500K
Input:	Universal 120-277V AC 50/60 Hz
Controls:	DMX512-A with DMX commissioning via RDM
Dimming:	Electronic low voltage (ELV) : 100 - 5% 0-10V: 100 - 1%
Maximum Delivered Intensity:	Up to 8600x2 cd (Spot 18°, 6500K, CRI 90)
Maximum Delivered Output:	Up to 1680x2 lm (Flood (A,B,C) 90°, 6500K, CRI 90)
Operating Temperature:	-13°F to 122°F (-25°C to 50°C)

Standards: IP65 rated, ETL & cETL wet location listed
Title 24 JA8-2016 Compliant

Warranty: 5 year WAC Lighting guaranteed warranty

BEAM ANGLES



S - 18°



N - 30°



F - 50°



F - 90°

FINISHES

Black
BKBronze
BZGraphite
GHWhite
WT

Beam	Beam Angle	Color Temp	Reference Output ¹			Light Direction
			CRI	Lumens	CBCP	
S Spot	18°	930 3000K	90	1455 x2	7555	S Straight
N Narrow	30°	930 3000K	90	1430 x2	2920	A Away
F Flood	50°	930 3000K	90	1385 x2	1540	B Towards
F Flood	90°	930 3000K	90	1515 x2	-	C One each

Reference output based on performance measured at 3000K.

CUBE

5” Double Wall Mount - Color Changing

DC-WD05

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

CONFIGURATION TABLE				
Model & Size	Beam	Light Direction	Color Temperature & CRI	Housing Finish
DC-WD05 (20W x2)	S - 18°	S - Straight	CC - Color Changing	BK - BLACK
	N - 30°	A - Away		BZ - BRONZE
	F - 50°	B - Towards		GH - GRAPHITE
	F - 90°	C - One each		WT - WHITE

DC-WD05-__-CC-__

Example: DC-WD05-FA-CC-GH

ORDERING NOTES	
1.	18°, 30°, and 50° beams can only be ordered with the Light Direction “S-Straight”.
2.	90° beam fixtures can only be ordered with the Light Directions “A-Away”, “B-Towards”, and “C-One each”.

CUBE

5" Double Wall Mount - Color Changing

DC-WD05

Fixture Type:

Project:

Catalog#:


Location:

PERFORMANCE DATA


Polar Candela Distribution Charts

Samples shown at 3000K


Spot Beam: 18°, Light Direction: Straight




Narrow Flood Beam: 30°, Light Direction: Straight



Flood Beam: 50°, Light Direction: Straight



Flood Beam: 90°, Light Direction: Away



Unified Glare Rating (UGR) Table

General performance of fixtures at 3000K and 90 CRI.

Beam	Angle	UGR Range
Spot	18°	≤ 17
Narrow Flood	30°	≤ 20
Flood - S	50°	≤ 20
Flood - A	90° - Away	≤ 32
Flood - B	90° - Towards	≤ 24
Flood - C	90° - One each	≤ 32