

FQ Tunable White
2" Adjustable


R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:


Project:

Catalog#:

Location:



LINE DRAWING



PRODUCT DESCRIPTION

FQ (Function + Quality) Experience simplicity and versatility with FQ 2" recessed luminaires. The fixtures merge modern design with world-class performance to achieve the ultimate in function and flexibility. Enjoy the benefits of two fixtures in one with Tunable White 1800-4000K and Dim-to-Warm 3000K-1800K features built into each luminaire, allowing you to customize the best light to illuminate dining areas, great rooms, primary bedrooms, kitchens, and baths on the fly. Deep regressed light sources deliver a glare-free, quiet ceiling aesthetic for a clean architectural look while providing a robust output from a diminutive source.

SPECIFICATIONS

Construction:	Durable die-cast self flanged aluminum construction
Mounting:	Heavy gauge retention clips support trim firmly Ceiling cut out: Trim Ø 3 1/2"  Trimless Ø 3 1/2"  Accommodates 1/2" - 1" ceiling thickness
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Input:	Universal 120-277V AC, 50/60 Hz
Dimming:	2CH 0-10V, DMX512-A: 100-0.1%
Maximum Delivered Intensity:	Up to 2,393 cd (Square Narrow Flood 30°, 18W, 4000K, CRI 90)
Maximum Delivered Output:	Up to 1,084 lm (Square Narrow Flood 30°, 18W, 4000K, CRI 90)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed, Title 24 JA8 Compliant
Warranty:	5 year WAC Lighting guaranteed warranty

BEAM ANGLES



FINISHES



Model	Beam	Lumens Ref Output*	CBCP	Color Temp	CRI
R2FRAT Round Trim	N 30° Round	980	2165	TW 1800K-4000K	90
R2FRAL Round Trimless	Square	985	2175		
R2FSAT Square Trim	F 42° Round	915	1310		
R2FSAL Square Trimless	Square	905	1310		
	W 55° Round	920	1025		
	Square	935	1035		

Lumens and CBCP are reference values for a trim fixture with 2 housing set to 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.

FQ Tunable White
2” Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

CONFIGURATION TABLE		
Model	Color Temperature	Reflector Finish
R2FRAT	TWA - 1800K-4000K	BK - BLACK
R2FRAL		DB - DARK BRONZE
R2FSAT		HZ - HAZE
R2FSAL		HZWT - HAZE/WHITE WT - WHITE

R2FRAT-TWA-
Example: R2FRAT-TWA-WT

ORDERING NOTES	
1.	The “Haze/White” finish is only available on trimmed fixtures (R2FRAT, R2FSAT).
2.	The “Haze” finish is only available on trimmless fixtures (R2FRAL, R2FSAL).
3.	Flood beam (F - 42°) reflector comes pre-installed. All three reflector options (N-30°, F-42°, and W-55°) are included.

FQ Tunable White
2" Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

HOUSINGS					
	Model	Control Options		Power	
New Construction IC Airtight - Round & Square Trim	R2FBNT-TW	X	DMX512-A	1	14W IC
		Z	0-10V	2	18W IC
New Construction IC Airtight - Round Trimless	R2FRNL-TW	X	DMX512-A	1	14W IC
		Z	0-10V	2	18W IC
New Construction IC Airtight - Square Trimless	R2FSNL-TW	X	DMX512-A	1	14W IC
		Z	0-10V	2	18W IC
Remodel Non-IC Round Trimless	R2FRRL-TW	X	DMX512-A	1	14W Non-IC
		Z	0-10V	2	18W Non-IC
Remodel Non-IC Square Trimless	R2FSRL-TW	X	DMX512-A	1	14W Non-IC
		Z	0-10V	2	18W Non-IC
Remodel IC Round & Square Trim	R2FBR2T-TW	X	DMX512-A	1	14W IC
		Z	0-10V		
Remodel Non-IC Round & Square Trim	R2FBRT-TW	X	DMX512-A	1	14W Non-IC
		Z	0-10V	2	18W Non-IC

ACCESSORIES	
LENS-11-HCM	Honeycomb Louver
LENS-11P-CRL-BK	Cross Louver
LENS-11AMB	Amber Lens
LENS-11RED	Red Lens
LENS-11BLU	Blue Lens
LENS-11GRN	Green Lens
LENS-11SPR	Spread Lens
LENS-11BEL	Beam Elongating Lens

R2F__-TW_-_
Example: R2FBNT-TWX-2

Millwork Housings	Size	Control Options		Power	
New Construction Round	A 0.8"	TWX	DMX512-A	1	15W IC
	B 1.5"	TWZ	0-10V	2	21W IC
New Construction Square	A 0.8"	TWX	DMX512-A	1	15W IC
	B 1.5"	TWZ	0-10V	2	21W IC

R2F__-_-TW_-_
Example: R2FRNM-A-TWZ-2

FQ Tunable White
2” Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:

Project:

Catalog#:

Location:

FEATURES

Optics: • High lumen output across the full Tunable White CCT range of 1800K - 4000K • Powerful glare control due to the fixtures 30° shielding angle, 35° vertical tilting, and 360° horizontal rotation	Construction: • Two piece die-cast aluminum constructed body and trim
LED: • High output COB LED with a 3-step Mac Adam ellipse • Rated operational life of 50,000 hours at L70 (LED maintains 70% of its initial delivered lumens when brand new for 50,000 hours of use.)	Trim and Reflector: • Reflectors with beam angles of 30°, 42°, and 55° are all included and swappable
Electrical: • Input power is universal 120-277VAC and 50/60 Hz • Available in 14W and 18W power levels	Installation: • Light engine is mounted onto the trim using springs that allow for easy replacement • Heavy gauge retention clips firmly support the trim within the housing
Dimming: • Electronic Low Voltage (ELV), TRIAC, and 0-10V dimming are available • ELV, TRIAC, and 0-10V are all capable of a range of 100 - 1%	Warranty: • WAC Architectural limited warranty up to 5 years • Full warranty found at: waclighting.com/warranty
Notes: • The White, Black, and Dark Bronze finishes are all electrostatically powder coated • The Haze finish is enamel coated	

FQ Tunable White
2" Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:

Project:

Catalog#:

Location:


PERFORMANCE DATA

Polar Candela Distribution Charts

Samples shown with a 18W fixture set to 3000K and 90 CRI.


ROUND

Narrow Flood Beam: 30° Beam




SQUARE


Narrow Flood Beam: 30° Beam




Flood Beam: 42° Beam




Flood Beam: 42° Beam



Wide Flood Beam: 55° Beam



Wide Flood Beam: 55° Beam



FQ Tunable White
2” Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:

Project:

Catalog#:

Location:

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

General performance of fixtures at 3000K and 90 CRI.

Round Fixture	Angle	UGR Range	Square Fixture	Angle	UGR Range
Narrow Flood	30°	≤22	Narrow Flood	30°	≤22
Flood	42°	≤23	Flood	42°	≤23
Wide Flood	55°	≤24	Wide Flood	55°	≤24

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

Lumens & CBCP Multiplier		Color Temperature					
TWA (1800K - 4000K)	Housing Power Level	1800K	2200K	2700K	3000K	3500K	4000K
	1 (14W)	0.59	0.69	0.76	0.80	0.85	0.88
	2 (18W)	0.74	0.86	0.95	1.00	1.06	1.10

FQ Tunable White
2" Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type:


Project:

Catalog#:


Location:

DIMENSIONAL DIAGRAMS


Round Trim (R2FRAT)




Round Trimless (R2FRAL)



Square Trim (R2FSAT)



Square Trimless (R2FSAL)




FQ Tunable White
2" Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL


Fixture Type: _____
Project: _____
Catalog#: _____
Location: _____

DIMENSIONAL DIAGRAMS


New Construction - Round Trim




New Construction - Round Trimless



New Construction - Square Trim



New Construction - Square Trimless




FQ Tunable White
2" Adjustable

R2FRAT | R2FRAL | R2FSAT | R2FSAL

Fixture Type: _____
Project: _____
Catalog#: _____
Location: _____

WIRING DIAGRAMS

DMX512-A



2CH 0-10V

