

Stealth Framing Projector

Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F

Fixture Type:


Project:

Catalog#:

Location:



LINE DRAWING



PRODUCT DESCRIPTION

The sleek, stylish luminaire projects a square, rectangular or circular area of light with crisp lines to frame or highlight art objects, providing maximum visual impact. Like a quality camera lens, the innovative projector contains adjustable lenses as well as shims to frame a sharp accenting light the width and length of the object. It can zoom in for a closeup or zoom out to frame larger pieces of art.

SPECIFICATIONS

Construction:	Die-cast aluminum with optical glass lenses
Mounting:	Track mounted; ceiling or wall mounted
Light Source:	Integrated LED, High output 3-step Mac Adam Ellipse Rated life of 50,000 hours at L70
Input:	120 VAC (WTK), 277 VAC (WHK), 120-277 VAC (MO)
Power:	24W
Dimming:	ELV, TRIAC (120V only): 100 - 5%
Maximum Delivered Intensity:	Up to 1,565 cd (4000K)
Maximum Delivered Output:	Up to 905 lm (4000K)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed
Warranty:	5 year WAC Lighting guaranteed warranty

FINISHES



Model	Color Temp		Lumens	CBCP	CRI
WTK-1224F WHK-122F MO-1224F	Ø2 9/16" Ø65mm	927 50°	873	1,448	90
		930 50°	920	1,525	
		935 50°	965	1,601	
		940 50°	992	1,647	



Stealth Framing Projector

Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

CONFIGURATION TABLE		
Model & Power	Color Temperature & CRI	Housing Finish
WTK-1224-F (120V)	927 - 2700K - 90	BK - BLACK
WHK-1224-F (277V)	930 - 3000K - 90	WT - WHITE
MO-1224-F (120-277V)	935 - 3500K - 90	
	940 - 4000K - 90	

W__-____-__

Example: WTK-1224-F940-BK

MO-1224-____-__

Example: MO-1224-F930-WT

ORDERING NOTES	
1.	The WTK-1224-F fixture is 120V and the WHK-1224-F fixture is 277V. Both fixtures are 24W and track mounted.
2.	The MO-1224-F fixture is a 24W and 120-277V ceiling mounted monopoint fixture.
3.	Fixtures with "F" in the model number are fixed in place and not adjustable.

Stealth Framing Projector

Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F

Fixture Type:

Project:

Catalog#:

Location:

FEATURES

Optics: - High definition zoomable projection with precision aiming - Armature capable of 360° horizontal rotation and 90° vertical aiming	Construction: Die-cast aluminum fixture with optical glass lenses
LED: - High output integrated LED with a 3-step Mac Adam ellipse - Rated operational life of 50,000 hours at L70 (LED maintains 70% of its initial delivered lumens when brand new for 50,000 hours of use.)	Trim and Reflector: Fixed beam at an angle of 50°
Electrical: - Input power is 120 VAC (WTK), 277 VAC (WHK), 120-277 VAC (MO) - Available in a 24W power level	Installation: - Track mounted (WTK, WHK) - Ceiling and wall mountable as a monopoint fixture (MO)
Dimming: - Electronic low voltage (ELV) and TRIAC dimming are available - ELV and TRIAC dimming are capable of a range of 100 - 5% at 120V only	Warranty: - WAC Architectural limited warranty up to 5 years - Full warranty found at: waclighting.com/warranty
Notes: The White and Black finishes are electrostatically powder coated	

Stealth Framing Projector

Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F

Fixture Type:

Project:

Catalog#:

Location:


PERFORMANCE DATA

Polar Candela Distribution Charts

Samples shown with a 24W fixture set to 3000K.

Fixed

Fixed Beam - 50°



Unified Glare Rating (UGR) Table

General performance of fixtures at 3000K and 90 CRI.

Round Fixture	Angle	UGR Range
Fixed	50°	≤0

Stealth Framing Projector

Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F


Fixture Type:

Project:

Catalog#:

Location:

DIMENSIONAL DIAGRAMS



Stealth Framing Projector


Large - Fixed

WTK-1224-F | WHK-1224-F | MO-1224-F

Fixture Type: _____
 Project: _____
 Catalog#: _____
 Location: _____

WIRING DIAGRAM

Schematic diagram of track inlet power connection.



Reference diagram for track and track connector circuit.

