

FQ Color Changing


4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type: _____
Project: _____
Catalog#: _____
Location: _____



LINE DRAWING



PRODUCT DESCRIPTION

Full Visible Spectrum color-tuning LEDs feature improved efficacy and lumens, as well as refined optical technology that offers human-centric recessed downlighting, catering to the needs of the modern technologist and integrator. Choose any color you can imagine, including the crispest white light or the softest pastel, with the ability to control gradients of saturated colors and a Tunable White CCT range from 1800-6500K.

SPECIFICATIONS

Construction:	Durable die-cast self flanged aluminum construction
Mounting:	Heavy gauge retention clips support trim firmly Ceiling cut out (Round): Trim $\varnothing 4\frac{3}{4}"$ Trimless $\varnothing 4\frac{3}{4}"$ Ceiling cut out (Square): Trim $4\frac{3}{4}" \times 4\frac{3}{4}"$ Trimless $4\frac{3}{4}" \times 4\frac{3}{4}"$ Accommodates $\frac{1}{2}" - 1"$ ceiling thickness
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Input:	Universal 120-277V AC, 50/60 Hz
Dimming:	DMX512-A RDM
Maximum Delivered Output:	Up to 1,355 lm (Round Asymmetric, 5000K)
Operating Temperature:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Wet location listed
Warranty:	5 year WAC Lighting guaranteed warranty

BEAM ANGLES



FINISHES



Model	Beam	Lumens	CBCP	Color Temp	CRI
R4FRWT Round Trim	A Asym	Round 1210 Square 1080	Ref Output* N/A N/A	CCX Color Changing	90+
R4FRWL Round Trimless					
R4FSWT Square Trim					
R4FSWL Square Trimless					

Lumens and CBCP are reference values for a trim fixture set to 3000K Color Temperature. Refer to Multiplier Table in Performance Data to determine other outputs.



FQ Color Changing
4” Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

CONFIGURATION TABLE		
Model	Color Temperature & CRI	Reflector Finish
R4FRWT	CC - Color Changing	BK - BLACK
R4FRWL		DB - DARK BRONZE
R4FSWT		HZ - HAZE
R4FSWL		HZWT - HAZE/WHITE
		WT - WHITE

R4FRWT-CC-__

Example: R4FRWT-CC-WT

ACCESSORIES	
LENS-16-HCM	Honeycomb Louver
LENS-16P-CRL-BK	Cross Louver
LENS-16AMB	Amber Lens
LENS-16RED	Red Lens
LENS-16BLU	Blue Lens
LENS-16GRN	Green Lens
LENS-16SPR	Spread Lens
LENS-16BEL	Beam Elongating Lens

ORDERING NOTES	
1.	The “Haze/White” finish is only available on trimmed fixtures (R4FRWT, R4FSWT).
2.	The “Haze” finish is only available on trimmless fixtures (R4FRWL, R4FSWL)

FQ Color Changing
4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type:

Project:

Catalog#:

Location:

ORDERING INFORMATION

Housings	Model	Power	Rating
New Construction Airtight Trimmed Round & Square	R4FBNT-CCX	15W	IC
New Construction Airtight Trimless Round	R4FRNL-CCX	15W	IC
New Construction Airtight Trimless Square	R4FSNL-CCX	15W	IC
New Construction Frame-In Trimmed Round & Square	R4FBFT-CCX	15W	Non-IC
New Construction Frame-In Trimless Round	R4FRFL-CCX	15W	Non-IC
New Construction Frame-In Trimless Square	R4FSFL-CCX	15W	Non-IC
New Construction Frame-In Trimmed Round & Square	R4FBFT-CCX	15W	Non-IC
New Construction Frame-In Trimless Round	R4FRFL-CCX	15W	Non-IC
New Construction Frame-In Trimless Square	R4FSFL-CC	15W	Non-IC

R4F__-CCX
Example: R4FBNT-CCX

FQ Color Changing

4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type:

Project:

Catalog#:

Location:


PERFORMANCE DATA

Polar Candela Distribution Charts

Samples shown from a trimmed fixture set to 3000K.


ROUND

Asymmetric Beam



SQUARE

Asymmetric Beam



FQ Color Changing
4" Wall Wash

R4FRWT | R4FRWL | R4FSWT | R4FSWL

Fixture Type:

Project:

Catalog#:

Location:

PERFORMANCE DATA

Unified Glare Rating (UGR) Table

UGR values shown are calculated using trimmed fixtures set to 3000K.

Round Fixture	Angle	UGR Range	Square Fixture	Angle	UGR Range
Asymmetric	-	≤26	Asymmetric	-	≤26

Lumens and CBCP Multiplier Table

Use the below table to determine lumens and CBCP values for the combinations of power, color temperature, and CRI values.

LUMENS AND CBCP MULTIPLIER								
Housing Wattage	Color Temperature							
	1800K	2200K	2700K	3000K	3500K	4000K	5000K	6500K
15W	0.70	0.86	0.97	1.00	1.04	1.08	1.12	1.10